

DRIVOL MAXPRO ATF

AUTOMATIC TRANSMISSION FLUID

ATF TYPE A SUFFIX A

Product Description:

Drivol Maxpro ATF Type A Suffix A, an automatic transmission fluid tailored for vehicles equipped with automatic transmission systems that demand General Motors TYPE A SUFFIX A quality fluids. Formulated with refined base oils and additive technology, it guarantees improved thermal stability, frictional properties, and safeguards against rust and corrosion.

Key Features:

- Excellent defense against rust and corrosion.
- Compatible with all commonly used seal materials.
- Supports lower maintenance cost
- Enhanced cold start performance with improved low temperature fluidity
- High shear stability maintains viscosity and oil film at high temperatures
- Reduces deposit formation and provides wear protection to vital components

Applications:

- Recommended for automatic transmissions and power steering systems of vehicles requiring General Motors Type A Suffix A quality fluids
- Suitable for manual transmissions and hydraulic systems requiring Type A Suffix A fluids

Specification / Recommendations:

International Standards & Meet the Requirements	
Type A Suffix A (TASA)	

Technical Data:

S. No.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.867
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	38.5
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	7.28
5	Viscosity Index	ASTM D2270	156
6	Flash Point COC (°C)	ASTM D92	210
7	Pour Point (°C)	ASTM D97	-39

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

