



DRIVOL MAXPRO CVT AUTOMATIC TRANSMISSION FLUID ATF CVT

Product Description:

Drivol Maxpro ATF CVT, a fully synthetic premium transmission fluid made from high-quality synthetic base oil and a specialized additive package. It is designed to offer unparalleled protection for both ATF and CVT transmission gearboxes, even in challenging situations.

Key Features:

- Optimum frictional properties for premium performance
- Swift air release and reduced foaming
- Enhanced film strength at high temperatures
- Exceptional control over soot and deposit formation
- Protection against wear and corrosion on metal parts
- Improved friction durability for a smoother & prolonged transmission life.

Applications:

• Recommended for use in continuously variable transmissions (CVT) with push belts and chain drives found in the majority of European, Asian, and American passenger cars and vans.

Specification / Recommendations:

International Standards & Meet the Requirements

BMW Mini cooper EZL 799, Dodge/Jeep NS-2, CVTF+4, Ford CVT23, CVT30/ Motor craft XT-7-QCFT, MERCON C; GM/Saturn DEX-CVT, Honda HMMF, HCF-2, MAZDA CVTF3320, Mercedes Benz 23620, Toyota TC, Volkswagen/Audi TL 52180, G 052180, G 052516

Technical Data:

S. No.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.852
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	34.2
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	7.10
5	Viscosity Index	ASTM D2270	177
6	Flash Point COC (°C)	ASTM D92	208
7	Pour Point (°C)	ASTM D97	-45

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.



