

DRIVOL MAXPRO ATF III

AUTOMATIC TRANSMISSION FLUID

ATF III

Product Description:

Drivol Maxpro ATF III is a superior automatic transmission fluid crafted with synthetic base oils and advanced additive technology. Designed to enhance performance, it promotes trouble free functioning of transmission systems, meeting or even exceeding the requirements of automatic transmission fluids.

Key Features:

- Exceptional oxidation and thermal stability
- Outstanding defense against rust and corrosion
- Enhanced seal compatibility with prolonged seal life & possibility of reduced oil leakage
- High Viscosity index ensures good oil film strength high operating temperatures and starting at low ambient temperatures
- Improved frictional properties enhance transmission efficiency & shifting performance, ensuring consistent and trouble-free operation

Applications:

- Recommended for all automatic and semi-automatic transmissions, as well as hydraulic systems in passenger cars and light commercial vehicles requiring Dexron III fluid as specified by the manufacturer.

Specification / Recommendations:

International Standards & Meet the Requirements

Dexron III, ALLISON C-4, Cat TO-2, Ford Mercon, MB 236.9/7/6/5/1, Volvo 97340 / 97341, ZF TE-ML 02F, 03D, 04D, 09, ZF TE-ML 11A/B, 14A/B 17C

Technical Data:

S. No.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.855
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	34.1
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	7.15
5	Viscosity Index	ASTM D2270	180
6	Flash Point COC (°C)	ASTM D92	206
7	Pour Point (°C)	ASTM D97	-45

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

