

DRIVOL Maxpro VI

AUTOMATIC TRANSMISSION FLUIDS

ATF VI

Product Description:

Drivol Maxpro VI is a premium quality fully synthetic automatic transmission fluid crafted to meet or exceed the stringent requirements of the DEXRON VI standard. It provides protection against wear, ensures smooth and less noisy operations, maintains viscosity in varying temperatures, offers consistent and robust performance for the automatic transmission systems.

Key Features:

- Prolonged transmission system life
- Excellent oxidation and thermal stability
- Outstanding low temperature fluid properties
- Exceptional resistance against sludge and deposit formation
- Extended fluid drains interval and transmission life span
- Offers superior protection against wear, rust and reliable friction properties.

Applications:

- Recommended for modern automatic transmissions and steering gears of passenger cars, vans and light commercial trucks where DEXRON-VI fluid is specified.

Specification / Recommendations:

International Standards & Meet the Requirements	
DEXRON VI	

Technical Data:

S. No.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.889
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	30.6
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	6.14
5	Viscosity Index	ASTM D2270	154
6	Flash Point COC (°C)	ASTM D92	206
7	Pour Point (°C)	ASTM D97	-45

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

