

# Drivol STOP Brake Fluid DOT 3

## Product Description:

**Drivol STOP DOT 3** is a glycol ether based hydraulic brake fluid, specifically formulated to deliver superior braking performance even under extreme conditions. It offers exceptional protection against wear and corrosion, thus extending the service life of system components, rendering it suitable for hydraulic clutch systems.

## Key Features:

- Minimizes swelling on rubber surfaces
- Anti-corrosive properties on all metal components.
- High boiling point that helps to reduce vapor locking tendency
- Provides excellent protection against wear and rust for internal components
- Maintains fluidity at low temperatures and demonstrates exceptional thermal stability

## Applications:

- Recommended for brake and clutch applications in cars, trucks, buses and motorcycles where FMVSS DOT 3 fluids are specified.

## Specification / Recommendations:

International Standards & Meet the Requirements	
FMVSS No 116 DOT3, SAE J1703, ISO 4925 Class 3	

## Technical Data:

S. No.	Characteristics	Test Method	Test Results
1	Density @ 20°C (g/ml)	ASTM D1298	1.040
2	Kinematic Viscosity @ - 40°C (cSt)	ASTM D445	1310
3	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	2.4
4	pH	ASTM D1287	9.0
5	Equilibrium Reflux Boiling Point (ERBP)	ASTM D1120	240
6	Wet Equilibrium Reflux Boiling Point (WERBP)	ASTM D1120	148

## Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

## Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

