

Drivol STOP Brake Fluid DOT 4

Product Description:

Drivol STOP DOT 4 sets the standard for excellence in automotive brake and clutch systems. Crafted with precision and adhering to the SAE J1704 and FMVSS 116 DOT4 specifications, this synthetic fluid guarantees superior performance across various temperature ranges. With attributes like effective wear and corrosion protection, moisture resistance, and high boiling points. Drivol Brake Fluid DOT 4 ensures peak braking efficiency.

Key Features:

- Prevent wear & corrosion of internal components
- Maintains viscosity at both low and high temperatures
- Exhibits a superior boiling point and high resistance to vapor lock
- Prevents oxidation, rust, and piston seal swelling
- High temperature resistance and minimal moisture absorption

Applications:

- Recommended for brake and clutch systems in all vehicles requiring DOT 4 Brake fluid.

Specification / Recommendations:

International Standards & Meet the Requirements

FMVSS 116 DOT 4; SAE J1703; SAE J1704; ISO 4925 Class 4

Technical Data:

S. No.	Characteristics	Test Method	Test Results
1	Density @ 20°C (g/ml)	ASTM D1298	1.040
2	Kinematic Viscosity @ - 40°C (cSt)	ASTM D445	1350
3	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	2.35
4	pH	ASTM D1287	8.65
5	Equilibrium Reflux Boiling Point (ERBP)	ASTM D1120	266
6	Wet Equilibrium Reflux Boiling Point (WERBP)	ASTM D1120	158

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.