



Drivol Nulife Diesel Engine oil SAE 10W-40 API CI-4 Plus

Product Properties

Drivol Nulife SAE 10W-40 API CI-4 Plus is a diesel engine oil formulated from mineral base oils and balanced additive system. The engine oil provides reliable protection for wide range of light duty engines (with DPF) and operating conditions, offers fuel economy benefit.

Product Features

- Excellent detergency and dispersancy properties.
- · Excellent thermal and oxidation stability.
- Long oil drain interval and low oil consumption.
- Reduced maintenance cost with improved engine protection.
- Improved cold flow properties and shear stability.
- Good engine cleanliness and protection against piston deposits.

Areas of Application

- Designed for light commercial vehicles to provide reliable engine protection in urban/city driving conditions and variable load applications.
- Suitable for most light duty, low emission engines especially those fitted with exhaust diesel particulate filters (DPF).

Specification / Recommendations

| International Standards & Meet the Requirements | | | |
|---|------------------------------|----------------------------------|--|
| API CI-4 PLUS | MB 228.3 | Volvo VDS-3 | |
| | Renault RLD-2 | MAN M3275 | |
| | JASO DH-1 | Deutz DQC-II & III | |
| | MTU 2.0 | Cummins CES 20078 & 20077 | |
| | Caterpillar ECF-2 & ECF-1 | Global DHD-1 | |
| | Mack EO-N / EO-M Plus & EO-M | Detroit Diesel DFS93K215& 93K214 | |

Technical Data

| S.NO. | Characteristics | Test Method | Test Results |
|-------|-----------------------------------|-------------|----------------|
| 1 | Appearance | Visual | Bright & Clear |
| 2 | Density @ 15°C (g/ml) | ASTM D1298 | 0.862 |
| 3 | Kinematic Viscosity @ 40°C (cSt) | ASTM D445 | 125 |
| 4 | Kinematic Viscosity @ 100°C (cSt) | ASTM D445 | 15.2 |
| 5 | Viscosity Index | ASTM D2270 | 125 |
| 6 | Flash Point COC (°C) | ASTM D92 | 230 |
| 7 | Pour Point (°C) | ASTM D97 | -30 |

Manufacturing

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposa

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.



