

Drivol Nulife Diesel Engine oil SAE 15W-40 API CI-4 Plus

Product Properties

Drivol Nulife SAE 15W-40 API CI-4 Plus is a high-performance diesel engine oil made from superior mineral base oils and balanced additive system to provide optimum engine performance in modern diesel engine under full range of temperatures. It delivers excellent soot and viscosity control, outstanding protection against wear and exceptional versatility for multiple engines makes.

Product Features:

- Advanced detergency/dispersancy.
- Improved viscosity control and oil pumpability.
- Reduces engine wear and excessive oil and fuel consumption.
- Optimal soot handling, delivers excellent wear protection and long oil life.
- High thermal and oxidation stability with reduced sludge build-up and deposits.
- The additive system delivers improved cleanliness and protection against rust & corrosion.

Areas of Application:

- Turbocharged and naturally aspirated diesel engines of major North American, European and Japanese manufacturers.
- Light and heavy-duty diesel trucks.
- Engines fitted with exhaust gas recirculation system and also for engines with open crankcase ventilation.
- Heavy duty engines used in mining, construction, agriculture and other off-road applications.

International Standards & Meet the Requirements			
API CI-4 PLUS	MB 228.3	Volvo VDS-3	
	Renault RLD-2	MAN M3275	
	JASO DH-1	Deutz DQC-II & III	
	MTU 2.0	Cummins CES 20078 & 20077	
	Caterpillar ECF-2 & ECF-1	Global DHD-1	
	Mack EO-N / EO-M Plus & EO-M	Detroit Diesel DFS93K215& 93K214	

Specification / Recommendations:

Technical Data

S.NO.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.877
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	118
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	14.5
5	Viscosity Index	ASTM D2270	125
6	Flash Point COC (°C)	ASTM D92	236
7	Pour Point (°C)	ASTM D97	-30

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.



