

## **Drivol Nulife**

### **Heavy Duty Diesel Engine oil**

### **SAE 15W-40 API CI-4/SL**

#### **Product Description:**

**DRIVOL Nulife SAE 15W-40 API CI-4/SL** stands out as a superior lubricant, meticulously crafted with mineral base oil stocks to cater to the needs of diesel engines, whether on-road or off-road. Engineered to endure the diverse range of pressures and temperatures typical in modern engines, this oil ensures comprehensive protection. Its remarkable capabilities extend to effective soot and viscosity management, alongside unparalleled defense against wear, rendering it an ideal choice for a variety of engines.

#### **Key Features:**

- Exceptional management of soot accumulation and oil thickening.
- Superb safeguarding against wear and prolonged oil longevity, especially in sophisticated engine technologies.
- Enhanced cleanliness and piston protection, surpassing the stringent criteria set by numerous OEMs.

#### **Applications:**

- Highly recommended for an extensive array of heavy-duty applications across various operational settings, including on-road transportation and off-road ventures such as mining, forestry, construction, and agriculture.

#### **Specification / Recommendations:**

<b>International Standards</b>	<b>OEM Approvals</b>	<b>Meet The Requirements</b>
API CI-4/SL	MB 228.3	DEUTZ DQC III-18
ACEA E7-22	RENAULT RLD-2	DETROIT DIESEL DFS 93K215
	MACK EO-N/EO-M Plus	VOLVO VDS-3
	CUMMINS CES 20076/77	CATERPILLAR ECF-2

#### **Technical Data:**

<b>S.No.</b>	<b>Characteristics</b>	<b>Test Method</b>	<b>Test Results</b>
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.880
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	113
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	15.2
5	Viscosity Index	ASTM D2270	141
6	Flash Point COC (°C)	ASTM D92	230
7	Pour Point (°C)	ASTM D97	-35

#### **Manufacturing:**

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

#### **Disposal:**

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.