

# Drivol Nulife Diesel Engine oil SAE 20W-40 API CI-4 Plus

## Product Properties

**Drivol Nulife SAE 20W-40 API CI-4 Plus** is a multigrade diesel engine oil blended from highly refined base stocks and selected additives to provide excellent detergency, dispersancy and anti-wear properties suitable for all naturally aspirated and turbocharged diesel engines. It is formulated for all Euro III and lower vehicles, as well as agricultural or civil works machinery.

## Product Features

- Reduced oil consumption and improved fuel efficacy.
- Neutralizes corrosive acids and protects corrosion & rust.
- Improved protection against cylinder bore polishing
- Prevent wear on cylinder liners that usually occurs in high-performance forced-induction engines.

## Areas of Application

- Suitable for use in heavy duty, light duty commercial vehicles and multi-utility vehicles fitted with high speed naturally aspirated or turbo charged diesel engines operating at low speed and high torque conditions.

## Specification / Recommendations

International Standards & Meet the Requirements		
API CI-4 PLUS	MB 228.3	Volvo VDS-3
	Renault RLD-2	MAN M3275
	JASO DH-1	Deutz DQC-II & III
	MTU 2.0	Cummins CES 20078 & 20077
	Caterpillar ECF-2 & ECF-1	Global DHD-1
	Mack EO-N / EO-M Plus & EO-M	Detroit Diesel DFS93K215& 93K214

## Technical Data

S.NO.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 29.5°C (g/ml)	ASTM D1298	0.885
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	125
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	14.5
5	Viscosity Index	ASTM D2270	117
6	Flash Point COC (°C)	ASTM D92	230
7	Pour Point (°C)	ASTM D97	-21

## Manufacturing

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

## Disposal

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

