

# Drivol Nulife

## Diesel Engine oil

### SAE 20W-50 API CI-4 Plus

#### Product Properties

**Drivol Nulife SAE 20W-50 API CI-4 Plus** is formulated with conventional base oil and a premium additive package. It provides enhanced protection against oil oxidation, viscosity loss due to shear and oil aeration. It also provides protection against catalyst poisoning, particulate filter blocking, engine wear, piston deposits, degradation of low and high temperature deposits and soot-related viscosity increase.

#### Product Features

- Cleans the engine parts and extends engine life.
- Good fluidity properties during cold starts.
- Reduces engine wear and excessive oil and fuel consumption.
- Outstanding resistance to oxidation allows longer oil change interval.

#### Areas of Application

- Suitable for Agricultural, Off-highway Construction & Mining vehicles requiring high quality diesel engine oil.
- Suitable for heavy and light duty diesel commercial vehicles operating under various conditions.
- Suitable for use in most of the modern emissions after treatment equipped diesel engines including Exhaust Gas Recirculation (EGR) and Diesel Particulate Filters (DPF).

#### Specification / Recommendations

International Standards & Meet the Requirements		
API CI-4 PLUS	MB 228.3	Volvo VDS-3
	Renault RLD-2	MAN M3275
	JASO DH-1	Deutz DQC-II & III
	MTU 2.0	Cummins CES 20078 & 20077
	Caterpillar ECF-2 & ECF-1	Global DHD-1
	Mack EO-N / EO-M Plus & EO-M	Detroit Diesel DFS93K215& 93K214

#### Technical Data

S.NO.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.880
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	173
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	18.9
5	Viscosity Index	ASTM D2270	124
6	Flash Point COC (°C)	ASTM D92	242
7	Pour Point (°C)	ASTM D97	-24

#### Manufacturing

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

#### Disposal

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

