

Drivol Nulife Diesel Engine oil SAE 30 API CF

Product Description:

Drivol Nulife SAE 30 API CF stands as a mono-grade diesel oil crafted from a refined blend of mineral base oils and a balanced additive system. This formulation delivers superior temperature deposit control and safeguarding against ring/liner wear. Ideal for consistent use in non-turbocharged older engine models.

Key Features:

- Remarkable wear resistance for enhanced engine longevity.
- Minimal ash content to deter deposit formation, maintaining cleanliness within engine lubrication system.
- Exceptional protection against rust and corrosion, safeguarding critical engine components.

Recommended Applications:

- Suited for diverse fleets, encompassing a mix of large to smaller diesel trucks alongside passenger vehicles.
- Recommended for heavy-duty equipment employed in construction, mining, or quarry operations.

Specification / Recommendations:

International Standards & Meet the Requirements	
API CF	

Technical Data:

S.NO.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 29.5°C (g/ml)	ASTM D1298	0.887
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	107
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	11.9
5	Viscosity Index	ASTM D2270	101
6	Flash Point COC (°C)	ASTM D92	244
7	Pour Point (°C)	ASTM D97	-12

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

