

Drivol Nulife Turbo Plus Diesel Engine oil SAE 10W-40 API CI-4 Plus

Product Properties

Drivol Nulife Turbo Plus SAE 10W-40 API CI-4 Plus is a high-performance diesel engine oil made from semi-synthetic formulation and balanced additive system for light to medium duty commercial vehicles. The engine oil provides reliable protection for wide range of light to medium duty engines (with DPF) and operating conditions, offers fuel economy benefit as well.

Product Features

- Outstanding protection against oil thickening, high temperature deposits, sludge build-up and oil degradation.
- Excellent anti-wear, anti-scurf, bore polishing and corrosion protection properties.
- Helps to reduce viscosity breakdown and oil consumption under heavy duty, high temperature operating conditions.
- Outstanding low temperature properties.
- Reduce fuel consumption without compromising engine protection or durability.
- Good engine cleanliness and protection against piston deposits.

Areas of Application

- Designed for light commercial vehicles to provide reliable engine protection in urban/city driving conditions such as stop-start and variable load applications. The additive technology helps protect the engine from soot related deposits which can be caused by high idle applications.
- Suitable for most light duty low emission engines, especially those fitted with exhaust diesel particulate filters (DPF).

Specification / Recommendations

International Standards & Meet the Requirements		
API CI-4 PLUS	MB 228.3	Volvo VDS-3
	Renault RLD-2	MAN M3275
	JASO DH-1	Deutz DQC-II & III
	MTU 2.0	Cummins CES 20078 & 20077
	Caterpillar ECF-2 & ECF-1	Global DHD-1
	Mack EO-N / EO-M Plus & EO-M	Detroit Diesel DFS93K215& 93K214

Technical Data

S.NO.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.872
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	108
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	14.5
5	Viscosity Index	ASTM D2270	138
6	Flash Point COC (°C)	ASTM D92	234
7	Pour Point (°C)	ASTM D97	-36

Manufacturing

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

