



Drivol Nulife Turbo Plus Diesel Engine oil SAE 15W-40 API CI-4 Plus

Product Properties

Drivol Nulife Turbo Plus SAE 15W-40 API CI-4 Plus is a high-performance diesel engine oil with semi synthetic formulation and balanced additive system, that adapts and protects under full range of pressures and temperatures found in modern diesel engines. It delivers excellent soot and viscosity control, outstanding protection against wear and rust with enhanced engine life and extended oil drain interval.

Product Features

- Ensures optimal soot handling, delivers excellent anti-wear properties and long oil life in advanced engines.
- Excellent emission control and extended performance protection.
- Protection from oil thickening and soot formation.
- Improved cleanliness and protection against piston deposit.

Areas of Application

- Turbocharged and naturally aspirated diesel engines of major North American, European, and Japanese manufacturers.
- Light, medium and heavy-duty diesel trucks.
- Engines fitted with exhaust gas recirculation system also for engines with open crankcase ventilation.
- Heavy duty engines used in mining, construction, agriculture and other off-road applications.

Specification / Recommendations

International Standards & Meet the Requirements			
API CI-4 PLUS	MB 228.3	Volvo VDS-3	
	Renault RLD-2	MAN M3275	
	JASO DH-1	Deutz DQC-II & III	
	MTU 2.0	Cummins CES 20078 & 20077	
	Caterpillar ECF-2 & ECF-1	Global DHD-1	
	Mack EO-N / EO-M Plus & EO-M	Detroit Diesel DFS93K215& 93K214	

Technical Data

S.NO.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.877
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	110
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	15.2
5	Viscosity Index	ASTM D2270	145
6	Flash Point COC (°C)	ASTM D92	232
7	Pour Point (°C)	ASTM D97	-36

Manufacturing

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposa

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.



