

Drivol Nulife Turbo Plus

Diesel Engine oil

SAE 15W-40 API CI-4

Product Description:

Drivol Nulife Turbo Plus SAE 15W-40 API CI-4 stands as a high-performance multigrade diesel engine oil, crafted with a semi-synthetic blend and advanced additives. It's engineered to cater to the diverse demands of heavy-duty diesel engines across various operational environments, ensuring superior performance and longevity for both the engine and the oil.

Key Attributes:

- **Acid Control:** Effectively mitigates acid buildup and chemical corrosion on engine bearings.
- **Enhanced Engine Cleanliness:** Employs cutting-edge detergent and dispersant additives to prevent oil thickening, sludge accumulation, and piston deposits, thereby guaranteeing optimal engine cleanliness and reliability.
- **Anti-Wear Protection:** Upholds a protective oil barrier between critical engine components such as pistons, rings, and cylinder walls across varying temperatures and pressures.
- **The soot dispersant additive** ensures the even dispersion of soot particles, curbing wear and prolonging engine efficiency and lifespan.

Applications:

- Ideally suited for modern low-emission engines, particularly those equipped with exhaust diesel particulate filters (DPF).

Specification / Recommendations:

International Standards	Meet The Requirements	
API CI-4	MB 228.3	Volvo VDS-3
ACEA E7	Renault RLD-2	MAN M 3275
	Mack EO-N/EO-M+	CAT ECF-1-a CAT ECF-2
	Cummins 20076/77/78	Deutz DQC-III-10
	MTU Type 2	Detroit Diesel DDC 93K215
	Global DHD-1	

Technical Data:

S.NO.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.873
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	105.6
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	14.8
5	Viscosity Index	ASTM D2270	145
6	Flash Point COC (°C)	ASTM D92	234
7	Pour Point (°C)	ASTM D97	-30

Manufacturing

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

