

# Drivol Nulife Turbo Plus Diesel Engine oil SAE 20W-40 API CI-4 Plus

## Product Properties

**Drivol Nulife Turbo Plus SAE 20W-40 API CI-4 Plus** is a multigrade diesel engine oil made with semi synthetic technology and balanced additive system, suitable for all diesel engines having naturally aspirated and turbocharged induction. It is formulated for all Euro-III and lower emission vehicles, as well as agricultural or civil works machinery.

## Product Features

- High detergent and dispersant properties prevent the formation of sludge in cold weather.
- Alkaline reserve ensures a long service life by neutralizing acids formed from the combustion of diesel with varying Sulphur content.
- Prevent wear of cylinder liners that usually occurs in high-performance forced-induction engines.

## Areas of Application

- Suitable for use in heavy duty commercial vehicles, light commercial vehicles and multi-utility vehicles fitted with high speed naturally aspirated or turbo charged diesel engines operating at low speed and high torque conditions prevalent in prolonged city stop and go driving conditions.

## Specification / Recommendations

International Standards & Meet the Requirements		
API CI-4 PLUS	MB 228.3	Volvo VDS-3
	Renault RLD-2	MAN M3275
	JASO DH-1	Deutz DQC-II & III
	MTU 2.0	Cummins CES 20078 & 20077
	Caterpillar ECF-2 & ECF-1	Global DHD-1
	Mack EO-N / EO-M Plus & EO-M	Detroit Diesel DFS93K215& 93K214

## Technical Data

S.NO.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 29.5°C (g/ml)	ASTM D1298	0.885
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	114
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	15.4
5	Viscosity Index	ASTM D2270	142
6	Flash Point COC (°C)	ASTM D92	230
7	Pour Point (°C)	ASTM D97	-30

## Manufacturing

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

## Disposal

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

