

Drivol Nulife Turbo Diesel Engine oil SAE 15W-40 API CF

Product Description:

Drivol Nulife Turbo SAE 15W-40 API CF is an advanced multigrade engine oil engineered with a semi-synthetic blend and a unique combination of additives tailored to meet the dynamic demands of diesel engines. Formulated with advanced dispersants, it effectively maintains engine cleanliness, prolongs oil drain intervals and enhances the engine's lifespan.

Key Features:

- Significantly reduces oil consumption by up to 30%, extends oil longevity and enhances fuel efficiency.
- High alkaline reserve aids in neutralizing acids, ensuring engine protection.
- Exhibits exceptional performance in low-temperature conditions.
- Demonstrates superior shear stability and viscosity retention, ensuring consistent performance.
- Provides comprehensive protection, promoting prolonged engine durability.

Applications:

- Suitable for a diverse range of turbocharged and naturally aspirated diesel engines.
- Particularly recommended for use in older Mercedes-Benz trucks and buses.
- Offers cost-effective lubrication for off-highway applications like agricultural tractors.
- Meets the recommendations of major automotive engine builders.

Specification / Recommendations:

International Standards & Meet the Requirements	
API CF	

Technical Data:

S.NO.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.881
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	103
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	14.5
5	Viscosity Index	ASTM D2270	145
6	Flash Point COC (°C)	ASTM D92	236
7	Pour Point (°C)	ASTM D97	-33

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

