

Drivol Nulife Turbo Diesel Engine oil SAE 20W-50 API CF

Product Description:

Drivol Nulife Turbo SAE 20W-50 API CF presents a specially crafted semi-synthetic multigrade engine oil and performance additives tailored to address the diverse requirements of diesel engines. This formulation is engineered to deliver superior protection and performance even in the most challenging conditions.

Key Features:

- Harnesses the advantages of multigrade engine oils.
- Maintains viscosity across the entire spectrum of operating temperatures.
- Extends oil lifespan while enhancing operating efficiency.
- Effectively manages acid formation, mitigating corrosion risks.

Applications:

- Suitable for a broad array of engines, including both turbocharged and non-turbocharged variants, in standard operating conditions.
- Offers cost-effective lubrication for off-highway usage, such as agricultural tractors.

Specification / Recommendations:

| International Standards & Meet the Requirements | |
|---|--|
| API CF | |

Technical Data:

| S.NO. | Characteristics | Test Method | Test Results |
|-------|-----------------------------------|-------------|----------------|
| 1 | Appearance | Visual | Bright & Clear |
| 2 | Density @ 15°C (g/ml) | ASTM D1298 | 0.882 |
| 3 | Kinematic Viscosity @ 40°C (cSt) | ASTM D445 | 160 |
| 4 | Kinematic Viscosity @ 100°C (cSt) | ASTM D445 | 19.2 |
| 5 | Viscosity Index | ASTM D2270 | 137 |
| 6 | Flash Point COC (°C) | ASTM D92 | 246 |
| 7 | Pour Point (°C) | ASTM D97 | -30 |

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

