

Drivol Prima Plus

Heavy Duty Diesel Engine oil

SAE 10W-30 API CK-4

Product Description:

Drivol Prima Plus SAE 10W-30 API CK4 represents an innovative synthetic blend engine oil engineered with triple protection technology. Specifically formulated to combat wear, deposits, and oil breakdown, this oil also delivers fuel economy benefits. Utilizing a combination of advanced additive technology and synthetic base oil, it ensures top-notch protection even under the most demanding conditions typical of modern, low-emission engines.

Key Features:

- Exceptional wear protection.
- Enhanced fuel economy and engine efficiency.
- Maintains optimal viscosity control and oil pressure with good shear stability.
- Protects against deposits, promoting cleaner engine operation throughout the oil drain interval.
- Ensures compliance with vehicle emission standards.

Applications:

- Recommended for heavy-duty engines, including those equipped with the latest emission control technologies such as Exhaust Gas Recirculation (EGR) and diesel particulate filters.
- Ideal for off-highway applications in sectors like agriculture, mining, logging, and construction, even in environments with high levels of fuel sulfur.
- Suitable for use in both naturally aspirated and turbocharged diesel engines.

Specification / Recommendations:

International Standards	Meet The Requirements	
API CK4	MB 228.31	CAT ECF-3
ACEA E7-22	Ford WSS-M2C171-F1	Cummins CES 20086
ACEA E11-22	Detroit Diesel DDC93K222	Mack EOS-4.5
	Volvo VDS 4.5	Renault VI RLD-3
	MAN 3575 MAN 3775	Deutz DQC III-18LA

Technical Data:

S.NO.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.863
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	81.8
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	12.1
5	Viscosity Index	ASTM D2270	141
6	Flash Point COC (°C)	ASTM D92	238
7	Pour Point (°C)	ASTM D97	-42

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

