

Drivol Prima Ultra Diesel Engine oil SAE 10W-30 API FA4

Product Description:

Drivol Prima Ultra SAE 10W-30 API FA4 is a synthetic blend engine oil that is carefully formulated with a precisely balanced additive system. Designed to protect low emission engines, particularly in challenging situations, it offers improved control over wear and deposits, as well as strong resistance to high temperatures.

Key Features:

- Unmatched all-season performance, adaptable to varying weather conditions.
- Utilizes cutting-edge technology to maintain engine cleanliness and minimize oil consumption.
- Ensures optimal engine longevity across all service scenarios.
- Features a lower HTHS viscosity compared to API CK-4 oils, maximizing fuel efficiency potential.

Applications:

- Ideal for off-highway applications including agricultural, mining, logging, and construction sectors.

Specification / Recommendations:

International Standards & Meet the Requirements	
API FA4	

Technical Data:

S.NO.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.878
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	68.0
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	10.7
5	Viscosity Index	ASTM D2270	147
6	Flash Point COC (°C)	ASTM D92	238
7	Pour Point (°C)	ASTM D97	-42

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

