

Drivol Prima Ultra Heavy Duty Diesel Engine oil SAE 5W-30 API FA-4

Product Description:

DRIVOL Prima Ultra SAE 5W-30 API FA-4 stands as a premier synthetic heavy-duty engine oil, boasting a "Low-SAPS" formula and an efficient additive system. Crafted to champion enhanced fuel economy and diminished emissions, this oil offers superior protection through synthetic technology, drastically reducing engine friction and extending drain intervals. Tailored to accommodate the most cutting-edge engine technologies, it sets a new standard in engine care.

Key Features:

- **Enhanced Fuel Economy:** By reducing High Temperature High Shear viscosity (HTHS), this oil optimizes fuel efficiency without compromising engine protection or longevity, resulting in substantial cost savings.
- **Low-Ash Formulation:** Its advanced low-ash formula prevents exhaust after treatment devices from blocking or becoming contaminated, ensuring ongoing compliance with emission regulations while maximizing fuel efficiency.
- **Extended Drain Intervals:** Designed to meet the rigorous demands of Euro-6 engines, it enables operators to optimize maintenance schedules, thus controlling maintenance costs effectively.
- **Superior Piston Cleanliness:** This oil maintains high levels of piston cleanliness, a crucial factor for ensuring the prolonged life of the engine.

Applications:

- **Versatile Usage:** Recommended for a wide array of heavy-duty applications, it extends oil life and service intervals even under severe operating conditions.
- **Euro-6 Compatibility:** Tailored to suit the latest Euro-6 engines, it offers unparalleled performance and reliability.

Specification / Recommendations:

International Standards	Meet The Requirements	
API FA-4	MB 228.61	Cummins CES 20087
	Detroit Diesel DFS 93K223	

Technical Data:

S.No.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.843
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	70.1
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	11.2
5	Viscosity Index	ASTM D2270	153
6	Flash Point COC (°C)	ASTM D92	236
7	Pour Point (°C)	ASTM D97	-45

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

