



Drivol Egon Plus Passenger Car Engine oil SAE 10W-30 API SN

Product Description:

Drivol Egon Plus SAE 10W-30 API SN is a high-quality multi-grade fully synthetic motor oil engineered to provide superior engine protection, even in the most challenging driving circumstances. It offers unparalleled safeguarding for contemporary engines, including efficient turbo-GDI (Gas Direct Injection) engines. Formulated with premium additive technology and premium petroleum-base stocks, Drivol Egon Plus SAE 10W-30 API SN ensures engines remain in optimal condition, maintaining peak performance.

Key Features:

- Low-ash detergency prevents the accumulation of carbon and sludge deposits.
- Exceptional performance in extreme conditions throughout all seasons.
- Shields emission systems from harm.
- Maximum resistance against oxidation and viscosity breakdown.

Applications:

• Suitable for year-round usage in engines running on gasoline, high-ethanol gasoline, and those without turbocharging and direct injection.

Specification / Recommendations:

International Standards	Meet the Requirements
APISN	GM Dexos 2
ILSAC GF-5	MB 229.52/229.51
ACEA C2/C3	VW 502.00/505.01
	BMW LL04
	JASO DL-1
	Porsche C30
	MTU Type 2.1
	Allison C4

Technical Data:

S.NO.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.855
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	62.9
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	11.2
5	Viscosity Index	ASTM D2270	173
6	Flash Point COC (°C)	ASTM D92	236
7	Pour Point (°C)	ASTM D97	-33

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.



DRIVOL GmbH, Am Seedamm 44, 60489 Frankfurt am Main Germany.

Phone: +49 69 15 32 696 621 | Fax: +49 69 36408970 | Website: www.drivol.de



