

Drivol Egon Plus

Passenger Car Engine oil

SAE 5W-20 API SN/ SN-RC

Product Properties

Drivol Egon Plus SAE 5W-20 API SN/SN-RC is a fully synthetic high-performance, low-viscosity engine oil of superior performance designed for the newest generation of engines of premium car manufactures. Tailored to deliver peak performance, it serves as an optimized solution for ensuring engine longevity and efficiency.

Key Features:

- Reduces operational costs and fuel consumption.
- Delivers outstanding performance in cold weather conditions.
- Exhibits exceptional thermal and oxidation stability, effectively slowing oil aging and extending drain intervals.
- Effectively minimizes engine deposits and optimizes the functionality of particulate filters, meet Euro VI emission standards.
- Shields engines from various impurities, actively combating sludge formation, thus maintain optimal performance over time.

Applications:

- Tailored for the latest generation of engines produced by premium car manufacturers.
- Recommended for use in all vehicles requiring 5W-20 viscosity grade engine oils under all driving conditions.

Specification / Recommendations:

| International Standards | Meet The Requirements |
|-------------------------|--------------------------------|
| API SN/SN- RC | FORD - 948-A/948-B |
| ACEA C5-21 | Jaguar- Land Rover JLR 03.5004 |
| ILSAC GF-5 | |

Technical Data:

| S.No. | Characteristics | Test Method | Test Results |
|-------|-----------------------------------|-------------|----------------|
| 1 | Appearance | Visual | Bright & Clear |
| 2 | Density @ 15°C (g/ml) | ASTM D1298 | 0.854 |
| 3 | Kinematic Viscosity @ 40°C (cSt) | ASTM D445 | 46.2 |
| 4 | Kinematic Viscosity @ 100°C (cSt) | ASTM D445 | 8.73 |
| 5 | Viscosity Index | ASTM D2270 | 170 |
| 6 | Flash Point COC (°C) | ASTM D92 | 228 |
| 7 | Pour Point (°C) | ASTM D97 | -45 |

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

