

Drivol Egon Passenger Car Engine oil SAE 5W-30 API SM

Product Description:

Drivol Egon SAE 5W-30 API SM is an advanced fully synthetic motor oil engineered to maintain engine performance at its peak, ensuring exceptional wear protection, cleaning power, and overall efficiency. Its formulation includes Low SAP additive chemistry to restrict sulphated ash and improved phosphorous retention.

Key Features:

- Enhanced frictional properties contribute to improved fuel economy.
- Minimizes corrosion, particularly in stop-start driving scenarios.
- Provides outstanding protection for high-performance engines.
- Controls high-temperature oxidation and deposits.

Applications:

- Recommended for use in naturally aspirated gasoline engines found in passenger cars, light commercial vehicles and portable power equipment where conventional passenger car motor oils are specified by the manufacturer.

Specification / Recommendations:

International Standards & Meet the Requirements

API SM

Technical Data:

S.NO.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.855
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	63
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	10.8
5	Viscosity Index	ASTM D2270	164
6	Flash Point COC (°C)	ASTM D92	226
7	Pour Point (°C)	ASTM D97	-39

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

