

Drivol Egon Plus Passenger Car Engine oil SAE 5W-30 API SN/CF

Product Description:

Drivol Egon Plus SAE 5W-30 API SN/CF stands out as an exceptionally high-performance, fully synthetic lubricant offering longlife engine performance and protection, with reliable engine cleanliness. Its superior formulation enhances responsiveness, ensuring the engine operates at peak efficiency until the subsequent oil change.

Key Features:

- Effectively eliminates sludge buildup in engines.
- Demonstrates long-term oxidation stability.
- Enhances fuel efficiency and facilitates smoother cold starts.
- Maintains optimal viscosity throughout the oil change interval.
- Diminishes oil volatility, reducing consumption and the necessity for frequent top-ups.

Applications:

• Ideal for fuel-injected gasoline engines equipped with 'blow-by' gas recirculation and catalytic converters, particularly in demanding driving conditions.

Specification / Recommendations:

International Standards	Meet The Requirements	
API SN/CF	BMW LL-04	GM DEXOS 2
ACEA C2/C3-21	MB 229.52/31/51/226.5	Renault RN 0700/0710

Technical Data:

S.No.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.840
3	Kinematic Viscosity @ 40°C(cSt)	ASTM D445	71.8
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	12.2
5	Viscosity Index	ASTM D2270	168
6	Flash Point COC (°C)	ASTM D92	215
7	Pour Point (°C)	ASTM D97	-39

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.



