

Drivol Egon Plus Passenger Car Engine oil SAE 5W-30 API SN PLUS

Product Description:

Drivol Egon Plus SAE 5W-30 API SN Plus is an advanced fully synthetic oil engineered to enhance overall engine performance. It effectively minimizes harmful emissions such as HC, NOx, and other particulates, ensuring longevity when paired with modern treatments like GPF and DPF. Its smooth flow provides outstanding protection against wear and maintains engine cleanliness. With excellent viscosity retention at low temperatures, it guards against corrosion and thermal breakdown.

Key Features:

- Fully compatible with all emission control devices.
- Reduces engine wear and corrosion.
- Shields against harmful deposits and acids.
- Extends oil life hence providing superior engine protection.
- Offers low-speed pre-ignition protection, particularly beneficial for modern turbocharged engines.

Applications:

- Meets or surpasses the latest API industry specifications for petrol engine oils, as well as the standards of numerous major American and European engine manufacturers.

Specification / Recommendations:

| International Standards & Meet the Requirements | |
|---|--|
| API SN Plus | |

Technical Data:

| S.NO. | Characteristics | Test Method | Test Results |
|-------|-----------------------------------|-------------|----------------|
| 1 | Appearance | Visual | Bright & Clear |
| 2 | Density @ 15°C (g/ml) | ASTM D1298 | 0.855 |
| 3 | Kinematic Viscosity @ 40°C (cSt) | ASTM D445 | 66 |
| 4 | Kinematic Viscosity @ 100°C (cSt) | ASTM D445 | 11.4 |
| 5 | Viscosity Index | ASTM D2270 | 168 |
| 6 | Flash Point COC (°C) | ASTM D92 | 240 |
| 7 | Pour Point (°C) | ASTM D97 | -39 |

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

