

Drivol Egon Plus Passenger Car Engine oil SAE 5W-40 API SN

Product Description:

Drivol Egon Plus SAE 5W-40 API SN is a lubricant enhanced with a performance proven additive system. This formulation safeguards engines across all operational scenarios by delivering superior wear control, even in intricate valve train mechanisms such as those with variable valve timing. Its ability to withstand temperature fluctuations contributes to prolonged engine life and allows for extended oil change intervals.

Key Features:

- Engine protection against wear and deposit accumulation.
- Optimal power and performance, especially in demanding driving conditions.
- Full compatibility with emission control systems and various gasoline grades.
- Extended oil change intervals and improved fuel economy.

Applications:

- Ideal for use in gasoline-powered automobiles and light-duty trucks.

Specification / Recommendations:

International Standards	Meet the Requirements
API SN	GM Dexos 2
ILSAC GF-5	MB 229.52/229.51
ACEA C2/C3	VW 502.00/505.01
	BMW LL04
	JASO DL-1
	Porsche C30
	MTU Type 2.1
	Allison C4

Technical Data:

S.NO.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.870
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	91
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	14.8
5	Viscosity Index	ASTM D2270	171
6	Flash Point COC (°C)	ASTM D92	230
7	Pour Point (°C)	ASTM D97	-39

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

