

Drivol Egon Plus

Passenger Car Engine oil

SAE 5W-40 API SN

Product Characteristics

Drivol Egon Plus SAE 5W-40 API SN incorporates premium performance synthetic base oils in combination with advanced additives ensuring optimal operation for high-performance engines. By safeguarding against power-draining deposits and minimizing wear, it maximizes engine efficiency. This oil is adept at maintaining its protective properties even during prolonged OEM-recommended drain intervals.

Key Features

- Eliminates sludge residue often left by subpar oils.
- Sustains protection throughout the entire oil-drain period.
- Protection from deposits, preserving power and performance.
- Enhances engine longevity by shielding surfaces from wear and neutralizing corrosive acids.

Applications

- Highly recommended for use in extreme climates (hot or cold) and under severe driving conditions to ensure maximum engine protection.
- Compatible with modern gasoline and gas engines, as well as gasoline/ethanol blends and biodiesel.
- Ideal for modern direct injection turbocharged gasoline engines, providing defense against damaging low-speed pre-ignition (LSPI).

Specification / Recommendations:

International Standards	OEM Approvals	Meet The Requirements
API SN	BMW LL-04	PORSCHE C40
ACEA C3-21	MB 229.52/31/51	Renault RN 0700/0710
	GM DEXOS 2	

Technical Data:

S.No.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.843
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	77.2
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	13.1
5	Viscosity Index	ASTM D2270	172
6	Flash Point COC (°C)	ASTM D92	235
7	Pour Point (°C)	ASTM D97	-39

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

