

Drivol Egon Ultra

Passenger Car Engine oil

SAE 0W-30 API SP-RC

Product Description:

Drivol Egon Ultra SAE 0W-30 API SP-RC is advanced synthetic oil, engineered to be the ultimate protection to the engine safeguarding from everyday wear and tear of driving. Made with cutting-edge synthetic technology, it provides exceptional protection over engine components, ensuring unparalleled protection against wear and oil degradation even in extreme temperature operations.

Key Features:

- Outstanding wear protection & enhanced fuel efficiency
- Improved Emission Control: Reduced levels of NOx, HC, and CO emissions.
- Facilitates smoother cold engine starts, even in frigid conditions.
- Delivers top-tier defense against wear and deposits immediately upon engine ignition.

Applications:

- Ideal for providing maximum safeguarding in both scorching heat and icy cold climates, as well as under demanding driving conditions.
- High performance passenger cars and light trucks
- Compatible with modern gasoline and gas engines, along with gasoline/ethanol blends and biodiesel.
- Specifically formulated for use in direct injection turbocharged gasoline engines necessitating protection against low-speed pre-ignition (LSPI).

Specification / Recommendations:

International Standards	Meet The Requirements
API SP/SP-RC	MB 227.61/229.61
ACEA C2-21	BMW LL- 12FE
ACEA A5/B5-21	FORD 952-A1
ILSAC GF-6	

Technical Data:

S.No.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.838
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	59.8
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	11.5
5	Viscosity Index	ASTM D2270	190
6	Flash Point COC (°C)	ASTM D92	218
7	Pour Point (°C)	ASTM D97	-42

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

