

# Drivol Egon Ultra Passenger Car Engine oil SAE 0W-40 API SP

**Product Description:**

Drivol Egon Ultra SAE 0W-40 API SP stands as a pinnacle in full synthetic lubricants, integrating cleansing technology to optimize the performance of high-powered engines. Its formulation shields engines from detrimental deposits and wear, thereby maximizing efficiency. Moreover, it diminishes engine friction, resulting in improved fuel economy.

**Key Features:**

- Prevents deposits, preserving their power and performance.
- Exhibits low oil consumption, necessitating less frequent top-ups.
- Prolongs engine lifespan by safeguarding surfaces from wear and corrosive acids.
- Eliminates sludge residue left behind by subpar oils, ensuring optimal engine cleanliness.
- Guard's high-performance engines, prevents deposits, preserving their power and performance.

**Applications:**

- Suitable for a wide range of engines including modern gasoline and gas engines.
- Provides maximum protection in both extreme hot and cold climates, as well as under severe driving conditions.
- Ideal for modern direct injection gasoline engines, offering defense against damaging low-speed pre-ignition (LSPI).

**Specification / Recommendations:**

International Standards	Meet The Requirements
API SP	MB 229.51/52
ACEA C3-21	Renault RN0700/RN0710

**Technical Data:**

S.No.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.838
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	80.2
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	14.0
5	Viscosity Index	ASTM D2270	181
6	Flash Point COC (°C)	ASTM D92	233
7	Pour Point (°C)	ASTM D97	-45

**Manufacturing:**

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

**Disposal:**

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

