

Drivol Egon Ultra Passenger Car Engine oil SAE 5W-30 API SP/SP-RC

Product Description:

Drivol Egon Ultra SAE 5W-30 API SP/ SP-RC stands out as top-tier fully synthetic engine oil engineered to deliver superior wear resistance and exceptional resilience against thermal breakdown, especially under high operating temperatures.

Key Features:

- Exceptional performance in both low and high-temperature conditions.
- Resists thermal breakdown even under extreme operating temperatures.
- Guards against harmful deposits and acids, promoting a cleaner engine operation.
- Engineered for superior engine protection and performance, surpassing conventional motor oils.

Applications:

- Tailored for the latest generation engines produced by premium car manufacturers.
- Ideal for use in direct injection turbocharged gasoline engines, offering protection against low-speed pre-ignition (LSPI) requirements.

Specification / Recommendations:

International Standards	Meet The Requirements
API SP/ SP-RC	MB 227.61/229.61
ACEA C2-21	Renault RN0700
ACEA A5/B5-21	
ACEA A7/B7-21	
ILSAC GF-6	

Technical Data:

S.No.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.840
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	62.8
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	10.8
5	Viscosity Index	ASTM D2270	165
6	Flash Point COC (°C)	ASTM D92	236
7	Pour Point (°C)	ASTM D97	-45

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.