

# Drivol Egon Ultra Passenger Car Engine oil SAE 5W-30 API SP

## Product Description:

**Drivol Egon Ultra SAE 5W-30 API SP** represents a distinctive engine oil blend, using fully synthetic base oils and advanced additive technology. Engineered to extend oil life, ensure superior engine protection, and optimized fuel efficiency. This formulation caters to the stringent demands of modern, high-performance engines. It is specifically designed for new generation engines operating at close tolerances, necessitating specialized low-viscosity oils, all while maintaining engine durability and reliability.

## Key Features:

- Exceptional protection across both low and high temperatures.
- Resilience against thermal breakdown, even under extreme heat conditions.
- Low viscosity and reduced friction for enhanced fuel efficiency.
- Defense against harmful deposits and acids, promoting engine cleanliness.
- Protection against low-speed pre-ignition (LSPI) in direct injection turbocharged gasoline engines.

## Recommended Applications:

- Suitable for use in both naturally aspirated and turbocharged gasoline engines in passenger vehicles requiring ILSAC GF-6 and API SP performance standards.
- Particularly well-suited for the latest "Downsized" Gasoline engines equipped with Stop & Start technologies, as well as hybrid engines that demand highly fluid synthetic engine oils.

## Specification / Recommendations:

International Standards & Meet the Requirements	
API SP / ILSAC GF-6	

## Technical Data:

S.NO.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.856
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	69
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	11.6
5	Viscosity Index	ASTM D2270	164
6	Flash Point COC (°C)	ASTM D92	230
7	Pour Point (°C)	ASTM D97	-45

## Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

## Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

