

Drivol Egon Ultra Passenger Car Engine oil SAE 5W-40 API SP

Product Description:

Drivol Egon Ultra SAE 5W-40 API SP is an advanced, fully synthetic engine oil engineered for exceptional performance. Utilizing innovative technology, it effectively reduces the formation of power-draining deposits and minimizes wear, enabling high-performance engines to operate at peak efficiency. Additionally, it reduces engine friction, enhancing fuel economy.

Key Features:

- Eliminates sludge residue left behind by previous inferior oils.
- Promotes low oil consumption, reducing the need for frequent top-ups.
- Guard high-performance engines against performance-degrading deposits.
- Prolongs engine lifespan by shielding surfaces from wear and neutralizing combustion acids.
- Provides outstanding protection and cleansing, even during extended oil-drain intervals recommended by manufacturers.

Applications:

- All types of vehicles, including high-performance turbo-charged, supercharged gasoline engines in passenger cars, SUVs, light vans and trucks.
- Suitable for use in modern direct injection turbocharged gasoline engines.

Specification / Recommendations:

International Standards	Meet The Requirements	
API SP	MB 229.52	BMW LL-04
ACEA C3-21	Renault RN0700/0710	OPEL OV 040 1547 - D40/G40

Technical Data:

S.No.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.855
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	85.4
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	14.2
5	Viscosity Index	ASTM D2270	173
6	Flash Point COC (°C)	ASTM D92	236
7	Pour Point (°C)	ASTM D97	-39

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

