

Drivol Uno

Passenger Car Engine oil

SAE 15W-40 API SL

Product Description:

Drivol Uno SAE 15W-40 API SL is an engine oil designed for mixed fleets, blending high-grade virgin mineral oils with advanced additives to accommodate various petrol engine designs. It promotes engine cleanliness, regulates the formation of high-temperature lacquers and low-temperature sludges and extends component lifespan through anti-wear technology. Additionally, it safeguards against oxidation, rust, and corrosion.

Key Attributes:

- Excellent viscosity retention over entire range of temperature.
- Effective wear and friction reduction properties.
- Facilitates easy cold starts and extends engine life
- Resistant to oxidation and thermally stable.

Applications:

- Recommended for a wide range of vehicles and engines, including commercial vehicles, buses, coaches, cars, vans, as well as plant and construction machinery, and agricultural equipment.

Specification / Recommendations:

International Standards	Meet The Requirements
API SL	ACEA A3/B3-16

Technical Data:

S.NO.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.871
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	115
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	14.5
5	Viscosity Index	ASTM D2270	128
6	Flash Point COC (°C)	ASTM D92	220
7	Pour Point (°C)	ASTM D97	-33

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

