

Drivol Uno Plus Passenger Car Engine oil SAE 15W-40 API SM

Product Description:

Drivol Uno Plus SAE 15W-40 API SM is a versatile mixed-fleet engine oil crafted from premium-quality virgin mineral oils and performance additives, tailored to suit various petrol engine configurations, including turbocharged models. It guarantees consistent lubrication across all operating conditions, while effectively preventing fouling and maintaining high viscosity levels.

Key Features:

- Demonstrates high thermo-oxidative stability, minimizing engine deposits and oil thickening.
- Supports extended oil change intervals.
- Exhibits high shear stability and maintains viscosity over time.
- Controls the formation of sludge, piston deposits, and soot accumulation.

Applications:

- Designed for a wide range of vehicle and engine types, including commercial vehicles, buses, coaches, cars, vans, as well as plant and construction machinery, and agricultural equipment.

Specification / Recommendations:

International Standards & Meet the Requirements	
API SM	

Technical Data:

S.NO.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.884
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	118
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	13.3
5	Viscosity Index	ASTM D2270	108
6	Flash Point COC (°C)	ASTM D92	226
7	Pour Point (°C)	ASTM D97	-27

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

