

Drivol Uno

Passenger Car Engine oil

SAE 20W-50 API SL

Product Characteristics:

Drivol Uno SAE 20W-50 API SL is a premium multigrade engine oil engineered to meet the API SL standards across all conditions encountered in passenger cars and light truck engines. Formulated with high viscosity index mineral oil, shear-stable polymer, and a carefully selected additive package, to ensure reliable engine protection even in the most demanding operating conditions.

Product Attributes:

- Exceptional regulation of oil thickening caused by soot, thanks to high-quality dispersants.
- Effectively controls wear and deposits, thereby enhancing engine longevity.
- Maintains optimal viscosity across a wide range of temperatures, safeguarding engine parts under varying conditions.
- Boasts prolonged oil life owing to its high Oxidation Stability.

Applications:

- Recommended for use in naturally aspirated and turbocharged gasoline engine vehicles, as well as light vans.
- Suitable for demanding operating conditions such as highways and congested city traffic throughout the year.
- Ideal for high-performance vehicles requiring motor oil meeting API SL performance standards.

Specification / Recommendations:

International Standards	Meet The Requirements
API SL	ACEA A3/B3-16

Technical Data:

S.NO.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.896
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	163.9
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	18.8
5	Viscosity Index	ASTM D2270	130
6	Flash Point COC (°C)	ASTM D92	234
7	Pour Point (°C)	ASTM D97	-24

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

