



# Drivol Uno Plus Passenger Car Engine oil SAE 20W-50 API SN/CF

## **Product Description:**

**Drivol Uno Plus SAE 20W-50 API SN/CF** is a premium engine oil engineered to surpass the latest lubrication demands of conventional mineral oils. This versatile formula delivers exceptional performance in gasoline and diesel (non-particulate filter equipped) vehicles, delivering outstanding protection across various driving conditions.

### **Key Features:**

- Enhances engine performance for optimized efficiency.
- Provides long-term protection against wear, extending the lifespan of engine components.
- Complies with a diverse array of car manufacturer's recommended oil change intervals.
- Exhibits high thermal and oxidation stability, ensuring reliable performance under challenging conditions.

# **Applications:**

- Ideal for use in passenger cars requiring multigrade oils.
- Suitable for both gasoline and diesel engines without diesel particulate filters.
- Designed to perform effectively in diverse driving environments such as city traffic, highways and rural roads across all seasons.

# **Specification / Recommendations:**

| International Standards | Meet The Requirements |  |
|-------------------------|-----------------------|--|
| API SN/CF               | VW 501 01/505 00      |  |
| ACEA A3/B4-21           | MB 229.1              |  |

### **Technical Data:**

| S.No. | Characteristics                   | Test Method | Test Results   |
|-------|-----------------------------------|-------------|----------------|
| 1     | Appearance                        | Visual      | Bright & Clear |
| 2     | Density @ 15°C (g/ml)             | ASTM D1298  | 0.883          |
| 3     | Kinematic Viscosity @ 40°C (cSt)  | ASTM D445   | 152.7          |
| 4     | Kinematic Viscosity @ 100°C (cSt) | ASTM D445   | 17.9           |
| 5     | Viscosity Index                   | ASTM D2270  | 130            |
| 6     | Flash Point COC (°C)              | ASTM D92    | 246            |
| 7     | Pour Point (°C)                   | ASTM D97    | -30            |

# **Manufacturing:**

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

### Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.



