

Drivol Uno

Passenger Car Engine oil

SAE 20W-40 API SF

Product Description:

Drivol Uno SAE 20W-40 API SF stands as a conventional multigrade engine oil, boasting a superior additive package that ensures peak engine protection during everyday driving. Its distinctive formulation, characterized by high shear stable viscosity, maintains an optimal oil layer between engine components, ensuring exceptional performance across diverse temperature ranges.

Key Features:

- Enhanced protection against wear for cylinder rings, liners, and valve trains.
- Guards against sludge, varnish, rust, and high-temperature thickening.
- Demonstrates outstanding oxidation and thermal stability.
- Facilitates extended oil drain intervals and promotes fuel efficiency.

Applications:

- Ideal for use in passenger cars, light trucks, SUVs, vans, gasoline-powered equipment, and moderate-duty engines, even under severe and varied operating conditions.
- Suitable for all gasoline engines requiring oils of SAE 20W-40 viscosity grade and up to API SF performance standards.

Specification / Recommendations:

| International Standards & Meet the requirements | |
|---|--|
| API SF | |

Technical Data:

| S.NO. | Characteristics | Test Method | Test Results |
|-------|-----------------------------------|-------------|----------------|
| 1 | Appearance | Visual | Bright & Clear |
| 2 | Density @ 15°C (g/ml) | ASTM D1298 | 0.892 |
| 3 | Kinematic Viscosity @ 40°C (cSt) | ASTM D445 | 125.2 |
| 4 | Kinematic Viscosity @ 100°C (cSt) | ASTM D445 | 14.8 |
| 5 | Viscosity Index | ASTM D2270 | 120 |
| 6 | Flash Point COC (°C) | ASTM D92 | 230 |
| 7 | Pour Point (°C) | ASTM D97 | -24 |

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

