

Drivol Uno

Passenger Car Engine oil

SAE 20W-50 API SF

Product Description:

Drivol Uno SAE 20W-50 API SF is a conventional multigrade engine oil designed to deliver reliable engine protection across a variety of demanding operating conditions. Crafted with carefully selected base stocks and a unique additive package, it excels in prolonging engine life by effectively managing wear and deposits.

Key Features:

- Enhances engine cleanliness, reducing maintenance costs.
- Exhibits excellent dispersancy and detergency properties.
- Maintains viscosity across operating temperatures for superior protection.
- High oxidation and thermal stability contribute to extended oil life.
- Provides improved defense against rust, corrosion, and acidic compounds.

Applications:

- Suitable for both naturally aspirated and turbocharged gasoline engines found in passenger cars and light commercial vehicles. Recommended for engines requiring a viscosity grade of 20W-50 and meeting API SF performance standards.

Specification / Recommendations:

International Standards & Meet the requirements	
API SF	

Technical Data:

S.NO.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.898
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	170.6
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	18.9
5	Viscosity Index	ASTM D2270	125
6	Flash Point COC (°C)	ASTM D92	238
7	Pour Point (°C)	ASTM D97	-27

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

