



Drivol Vita Passenger Car Engine oil SAE 20W-40 API SF

Product Description:

Drivol Vita SAE 20W-40 API SF is a versatile heavy-duty lubricant tailored to suit a diverse array of passenger car engines and light industrial vehicles. Formulated with an optimal blend of high-quality mineral and synthetic base stocks, along with a precisely balanced additive system, it delivers exceptional engine protection and performance.

Key Features:

- Ensures robust engine protection.
- Promotes hassle-free operation.
- Enhances resistance to oxidation.
- Exhibits outstanding anti-wear properties.
- Boasts low volatility, potentially extending drain intervals.

Applications:

- Ideal for use in passenger cars, light trucks, SUVs, vans, gasoline-powered equipment, and moderate-duty engines subjected to diverse and demanding operating conditions.
- Recommended for all gasoline engines requiring oils with SAE 20W-40 viscosity grading and up to API SF performance standards.

Specification / Recommendations:

J113.		
	International Standards & Meet the requirements	
	API SF	

Technical Data:

S.NO.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.880
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	103.6
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	15.2
5	Viscosity Index	ASTM D2270	154
6	Flash Point COC (°C)	ASTM D92	224
7	Pour Point (°C)	ASTM D97	-27

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.



