

Drivol Vita Sport Plus Passenger Car Engine oil SAE 10W-40 API SN/CF

Product Description:

Drivol Vita Sport Plus SAE 10W-40 API SN/CF stands as a semi-synthetic lubricant with an advanced formula to bolster engine performance. Engineered to combat engine sludge accumulation and wear, it caters to a diverse range of vehicles, delivering optimal performance under typical driving conditions.

Key Features:

- Safeguards against detrimental performance-inhibiting deposits.
- Shields modern turbocharged direct injection gasoline engines from harmful low-speed pre-ignition (LSPI).
- Enhances engine longevity by thwarting wear.
- Ensures consistent protection throughout the oil-drain cycle.
- Versatile application, suitable for gasoline, diesel, or gas engines, as well as biodiesel and gasoline/ethanol blends.

Applications:

- Compatible with gasoline, diesel, and gas engines, and adept for use with biodiesel and gasoline/ethanol blends.
- Ideal for modern direct injection turbocharged gasoline and diesel engines.

Specification / Recommendations:

| International Standards | Meet The Requirements | |
|-------------------------|-----------------------|---------------------|
| API SN/CF | PSA B71 2300 | Renault RN0700/0710 |
| ACEA A3/B4-21 | MB 229.3 | |

Technical Data:

| S.No. | Characteristics | Test Method | Test Results |
|-------|-----------------------------------|-------------|----------------|
| 1 | Appearance | Visual | Bright & Clear |
| 2 | Density @ 15°C (g/ml) | ASTM D1298 | 0.863 |
| 3 | Kinematic Viscosity @ 40°C (cSt) | ASTM D445 | 92.4 |
| 4 | Kinematic Viscosity @ 100°C (cSt) | ASTM D445 | 13.9 |
| 5 | Viscosity Index | ASTM D2270 | 153 |
| 6 | Flash Point COC (°C) | ASTM D92 | 242 |
| 7 | Pour Point (°C) | ASTM D97 | -39 |

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

