

Drivol Vita Sport

Passenger Car Engine oil

SAE 15W-40 API SL

Product Description:

Drivol Vita Sport SAE 15W-40 API SL stands out as a high-performance multi-grade engine oil, meticulously crafted to meet the latest API classifications. This motor oil incorporates potent anti-wear technology, ensuring optimal component longevity while providing robust defense against oxidation, rust, and corrosion.

Key Features:

- High thermal and oxidation stability.
- Exhibits minimal evaporation, leading to reduced oil consumption
- Facilitates extended oil change intervals, safeguarding natural resources
- Delivers superior performance compared to conventional mineral-based oils

Applications:

- Ideal for use in passenger cars, SUVs, light trucks, and vans equipped with gasoline engines requiring a viscosity grade of 15W-40 and meeting the API SL performance standard.

Specification / Recommendations:

International Standards	Meet The Requirements
API SL	ACEA A3/B3-16

Technical Data:

S.NO.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.883
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	108.2
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	15.5
5	Viscosity Index	ASTM D2270	151
6	Flash Point COC (°C)	ASTM D92	228
7	Pour Point (°C)	ASTM D97	-30

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

