

# Drivol Vita Sport

## Passenger Car Engine oil

### SAE 20W-50 API SL

#### Product Description:

**Drivol Vita Sport SAE 20W-50 API SL** is a semi-synthetic oil meticulously crafted to offer unparalleled protection in challenging environments. It blends top-grade hydrotreated mineral and synthetic base oils with a carefully selected additive package.

#### Key Attributes:

- Demonstrates exceptional thermo-oxidative stability.
- Exhibits low volatility, minimizing oil consumption and hydrocarbon emissions.
- Possesses robust dispersancy, resulting in minimal deposits and sludge formation.
- Boasts outstanding detergency properties.

#### Recommended Usage:

- Ideal for gasoline engines in passenger vehicles and light-duty commercial vehicles.

#### Specification / Recommendations:

| International Standards | Meet The Requirements |
|-------------------------|-----------------------|
| API SL                  | ACEA A3/B3-16         |

#### Technical Data:

| S.NO. | Characteristics                   | Test Method | Test Results   |
|-------|-----------------------------------|-------------|----------------|
| 1     | Appearance                        | Visual      | Bright & Clear |
| 2     | Density @ 15°C (g/ml)             | ASTM D1298  | 0.875          |
| 3     | Kinematic Viscosity @ 40°C (cSt)  | ASTM D445   | 172.3          |
| 4     | Kinematic Viscosity @ 100°C (cSt) | ASTM D445   | 20.8           |
| 5     | Viscosity Index                   | ASTM D2270  | 142            |
| 6     | Flash Point COC (°C)              | ASTM D92    | 226            |
| 7     | Pour Point (°C)                   | ASTM D97    | -33            |

#### Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

#### Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

