

Drivol Vita Sport Ultra Passenger Car Engine oil SAE 5W-30 API SP

Product Description:

Drivol Vita Sport Ultra SAE 5W-30 API SP represents an eco-conscious, semi-synthetic motor oil engineered to deliver top-notch engine defense for a wide range of vehicles, including turbocharged direct injection models, standard gasoline-powered cars, and light trucks, across various driving scenarios. Crafted from a mixture of synthetic and highly refined virgin base stocks, it ensures superior wear protection, combats sludge and varnish buildup, and remains resilient against viscosity and thermal degradation, even amidst rigorous usage. This semi-synthetic blend offers heightened performance advantages in extreme temperature conditions compared to traditional engine oils, furnishing additional security across all driving environments.

Key Features:

- Facilitates effortless cold starts.
- Promotes superior engine cleanliness, optimizing engine efficiency.
- Maintains viscosity stability across the entire temperature range.
- Extends the lifespan of catalytic converters and particulate filters.
- Provides exceptional protection against rust and corrosion.

Applications:

• Suitable for use in all gasoline engines requiring SAE 5W-30, including turbocharged gasoline direct injection vehicles and gasoline hybrid cars meeting API SP specifications.

Specification / Recommendations:

International Standards & Meet the Requirements
API SP / ILSAC GF-6

Technical Data:

S.NO.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.856
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	70
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	11.3
5	Viscosity Index	ASTM D2270	155
6	Flash Point COC (°C)	ASTM D92	234
7	Pour Point (°C)	ASTM D97	-42

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.



