



Drivol Maxpro EP 220 Industrial Gear Oils ISO VG 220

Product Description:

Drivol Maxpro ISO VG 220 is a heavy-duty industrial gear oil formulated with premium quality base stocks & additives engineered to withstand extreme pressure conditions. It's specifically designed to lubricate heavily loaded enclosed gear drives operating under moderate to severe service conditions.

Key Features:

- Exhibits low foaming with excellent air release properties.
- Demonstrates compatibility with various paint materials.
- Provides outstanding protection against corrosion and rust.
- Resists filter plugging, even in the presence of water.
- Offers a high load-carrying capacity, safeguarding against scuffing and wear.

Applications:

- Ideal for lubricating spur and helical gears, as well as some lightly loaded worm-type gear applications.
- Highly recommended across a diverse range of Industrial, Agricultural, and Commercial settings that necessitate EP Gear Oil.

Specification / Recommendations:

International Standards & Meet the Requirements

DIN 51517: Part 3, ISO 12925-1 CKD

Technical Data:

| S. No. | Characteristics | Test Method | Test Results |
|--------|-----------------------------------|-------------|----------------|
| 1 | Appearance | Visual | Bright & Clear |
| 2 | Density @ 15°C (g/ml) | ASTM D1298 | 0.896 |
| 3 | Kinematic Viscosity @ 40°C (cSt) | ASTM D445 | 222 |
| 4 | Kinematic Viscosity @ 100°C (cSt) | ASTM D445 | 19.6 |
| 5 | Viscosity Index | ASTM D2270 | 100 |
| 6 | Flash Point COC (°C) | ASTM D92 | 238 |
| 7 | Pour Point (°C) | ASTM D97 | -24 |

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

