

DRIVOL TRANSFLUID 150

Hydraulic Oil

ISO VG 150

Product Description:

Drivol Transfluid 150 is a high-quality hydraulic fluid crafted for hydraulic systems operating across diverse temperature and pressure ranges. Comprised of premium base oils and unique additives, it guarantees optimal performance and protection for hydraulic equipment.

Key Features:

- Fast air release & enhanced demulsibility
- Excellent anti- wear & corrosion protection
- Reduces downtime and maintenance expenses
- Good thermal stability & Excellent wear protection
- Protection from the formation of harmful sludge and deposit
- Promotes longer operating life, less maintenance and lowered operating costs.

Applications:

- Recommended for high pressure hydraulic power systems and a wide array of circulation systems of industrial and automotive equipment.
- Suitable for use in general manufacturing, power and metal equipment operating at high speeds, loads and temperatures like presses, injection molding, machine tools, etc.

Specification / Recommendations:

International Standards & Meet the Requirements

DIN 51524-part II, ISO 6743 HM, Parker (formerly Denison) HF-0, HF-1, HF-2, Cincinnati Machine P-68, P-69, and P-70

Technical Data:

S. No.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.895
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	152
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	15.0
5	Viscosity Index	ASTM D2270	98
6	Flash Point COC (°C)	ASTM D92	244
7	Pour Point (°C)	ASTM D97	-15

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

