

DRIVOL TRANSFLUID 68

Hydraulic Oil

ISO VG 68

Product Description:

Drivol Transfluid 68 is a high-performance hydraulic oil formulated with mineral base oil and anti-wear additives to provide excellent protection and performance in hydraulic systems. This oil is designed for use in industrial and mobile service applications where ISO VG 68 oils are recommended.

Key Features:

- Outstanding thermal & oxidation stability
- Excellent anti-wear & corrosion protection
- Improved demulsibility & anti foam properties
- Extended oil drain interval and components lifespan
- Guards against sludge formation for enhanced system cleanliness

Applications:

- Recommended for hydraulic systems and hydraulic pumps in stationary as well as mobile equipment's under various operating conditions.
- Suitable for circulation, splash, bath and ring oiling systems of both plain and anti-friction bearings, gears of industrial machinery, chain drives and crankcase Lubrication.

Specification / Recommendations:

International Standards & Meet the Requirements

DIN 51524-part II, ISO 6743 HM, Parker (formerly Denison) HF-0, HF-1, HF-2, Cincinnati Machine P-68, P-69, and P-70

Technical Data:

S. No.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.892
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	68.6
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	8.86
5	Viscosity Index	ASTM D2270	101
6	Flash Point COC (°C)	ASTM D92	234
7	Pour Point (°C)	ASTM D97	-15

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

