

Drivol Miles 2T Motorcycle Oil SAE 30 API TC

Product Description:

Drivol Miles 2T SAE 30 API TC, a conventional engine oil designed specifically for 2-stroke scooter engines equipped with premix or injector lube systems. Engineered to excel in high rpm conditions, this oil is fortified with robust additives to enhance oil film durability and provide superior anti-wear protection, effectively minimizing smoke and deposits.

Key Features:

- Exceptional wear and rust resistance.
- Reliable thermal and oxidation stability.
- Enhanced control over sludge buildup and corrosion.
- Ensures peak performance, maintaining engine cleanliness.

Applications:

- Ideal for motorcycles, snowmobiles, and chain saws that operate on a lean oil-to-fuel ratio.

Specification / Recommendations:

International Standards & Meet the Requirements	
API TC/ JASO FC	

Technical Data:

S. No.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.868
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	67.5
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	10.2
5	Viscosity Index	ASTM D2270	138
6	Flash Point COC (°C)	ASTM D92	240
7	Pour Point (°C)	ASTM D97	-27

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

