

Drivol Miles 4T Motorcycle Oil SAE 20W-50 API SL

Product Description:

Drivol Miles 4T SAE 20W-50 API SL, a conventional motorcycle engine oil engineered specifically for four-stroke motorcycles equipped with wet clutch systems. This oil ensures reliable transmission performance and optimal engine protection, even in challenging conditions such as extreme temperatures and high-speed operation.

Key Features:

- Remarkable cold start capabilities.
- Enhanced control over sludge buildup.
- Exceptional resistance to foaming and corrosion.
- Improved engine efficiency and fuel economy.
- Consistent shear stability and viscosity maintenance.

Applications:

- Ideal for use in four-stroke motorcycle engines across various brands, including American, Japanese, European, and Indian motorcycles requiring API SL performance standards.

Specification / Recommendations:

International Standards & Meet the Requirements	
API SL/ JASO MA2	

Technical Data:

S. No.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.882
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	165
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	18.5
5	Viscosity Index	ASTM D2270	126
6	Flash Point COC (°C)	ASTM D92	238
7	Pour Point (°C)	ASTM D97	-30

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

