



Drivol Photon Racing 4T Motorcycle Oil SAE 10W-50 API SN

Product Description:

Drivol Photon Racing 4T SAE 10W-50 API SN, fully synthetic motorcycle engine oil designed to unlock peak performance from the engine. Engineered for unparalleled protection and performance across varying temperatures, it elevates both power delivery and acceleration whether navigating in streets or dominating the race track.

Key Features:

- Provides long-term protection against engine wear.
- Meets the requirements of catalyst-equipped engines.
- Exhibits excellent shear stability to prevent viscosity breakdown.
- Utilizes race-derived formulation for maximum engine acceleration.
- Offers superior bearing protection even under extreme performance and racing conditions.

Applications:

• Ideal for use in all American, Japanese, European, and Indian motorcycles.

Specification / Recommendations:

| • | | |
|---|---|--|
| | International Standards & Meet the Requirements | |
| | API SN/ JASO MA2 | |

Technical Data:

| S. No. | Characteristics | Test Method | Test Results |
|--------|-----------------------------------|-------------|----------------|
| 1 | Appearance | Visual | Bright & Clear |
| 2 | Density @ 15°C (g/ml) | ASTM D1298 | 0.860 |
| 3 | Kinematic Viscosity @ 40°C (cSt) | ASTM D445 | 120 |
| 4 | Kinematic Viscosity @ 100°C (cSt) | ASTM D445 | 18.2 |
| 5 | Viscosity Index | ASTM D2270 | 167 |
| 6 | Flash Point COC (°C) | ASTM D92 | 240 |
| 7 | Pour Point (°C) | ASTM D97 | -36 |

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.



